



- Intel® Celeron® Processor N5105 4M Cache, up to 2.90 GHz
- Supports four USB 3.0 ports & Two USB 2.0
- Triple Display: DP + HDMI & VGA
- Low consumption & Fanless design

- M.2
- HDMI
- VGA
- TRIPLE DISPLAY
- BLUETOOTH
- VESA
- DP
- x6 3.0 / 2.0 USB
- RJ-45
- WIFI



# DataSheet :iX PC -Thin Client

Processor	Intel® Celeron® Processor N5105 4M Cache, up to 2.90 GHz	
Operating System	Windows 10 IoT Enterprise 2019 LTSC – Support Linux – Support Windows 11	
Storage	128 GB M.2 SATA Up to 512 GB	
Memory	Up to 32GB RAM DDR4 2 x SODIMM DDR4	
Input / Output ports	Front Panel	1x Power button, power LED 2 x USB 3.0 port 2 x USB 2.0 port 1 x microphone(3.5mm) ; 1 x headphone(3.5mm)
	Rear Panel	1 x RJ45 2 x USB 3.0 1 x VGA 1 x HDMI 2.0 1 x Display Port1.4 1 x DC_IN (12V)
Resolution	HDMI - Up to 4096x2160@60Hz DP: Up to 4096x2160@60Hz VGA- Up to 1920x1080@60Hz	
Audio	Stereo Audio Output - 3,5 mm (1/8 inch) Audio-Out Jack; 16-bit Stereo, Microphone Input - 3,5 mm (1/8 inch),	
Network	RJ 45 : 10:100:1000 Optional Wi-Fi & BT (m.2 PCIe port)	
Environment	Temperature range: Operating - 0°C to 40°C (32°F to 104°F) Storage - 0°C to 60°C (32°F to 140°F) Humidity: Operating - 20 to 80% non condensing; Storage – 10 to 90% non condensing Altitude: 0 to 20,000 ft	
Dimensions	123*123*45mm	
weight	450 gr	
Power	Device input: 100~240VAC@50/60HZ Device Output: 12VDC/5A external power adapter	
Security	Built-in Kensington security slot (cable sold separately)	
Warranty	Three-year hardware warranty Optional extended Warranty for years 4 & 5.	

FRONT SIDE VIEW	
1	Power button, power LED
2	USB 3.0 ports * 2
3	USB 2.0 ports * 2
4	Audio Out /Mic In
5	Kensington Lock



REAR SIDE VIEW	
1	RJ 45
2	USB 3.0 ports * 2
3	VGA
4	HDMI
5	DP

